

Projection parameters of Austria

Contributed by h.k.
Thursday, 14 December 2006
Last Updated Tuesday, 21 August 2007

Projection parameters of spatial data in Austria for data transformations.

Fundamental information about spatial data transformation: Proj4

Compilation of world-wide transformation parameters: EPSG

Open source utility for spatial data transformation: GDAL

EPSG-transformation parameters

MGI (Militaergeographisches Institut) alias Hermannskogel - Austria:

MGI to WGS84 (7-parameter transformation, accuracy of 1.5 meter)

X-axis translation 577,326 meter

Y-axis translation 90,129 meter

Z-axis translation 463,919 meter

X-axis rotation 5,137 arc-second

Y-axis rotation 1,474 arc-second

Z-axis rotation 5,297 arc-second

scale difference 2,4232 parts per million

Please check always EPSG for newer version of transformation parameters!

For raster transformation by `gdal_translate/gdalwarp` or vector transformation by `ogr2ogr` you have to include

```
TOWGS84[577.326,90.129,463.919,5.137,1.474,5.297,2.4232]
```

into the projection parameters of spatial data in Austria. You can also use the following WKT-files:

Austria_BMN_MGI_M28.prj	Bundesmeldenetz Meridian 28
Austria_BMN_MGI_M31.prj	Bundesmeldenetz Meridian 31
Austria_BMN_MGI_M34.prj	Bundesmeldenetz Meridian 34
Austria_GK_MGI_M28.prj	Gauss-Krueger Meridian 28
Austria_GK_MGI_M31.prj	Gauss-Krueger Meridian 31
Austria_GK_MGI_M34.prj	Gauss-Krueger Meridian 34

Austria_MGI_Lambert.prj Lambert

For Germany you can use the following WKT-file:

DHDN_zone4.prj DHDN Zone 4 (e.g. for Bavaria)

For Italy you can use the following WKT-files:

Italy_montemario.prj Italy Gauss-Boaga (northern part of Italy)

italy_etrf1989.prj Italy ETRF 1989 (northern part of Italy)

example for raster transformation with gdal:

(for syntax and supported formats please see the gdal-manuals)

source: ortho.tif/ortho.tfw in Bundesmeldenetz M28

target: Gauss-Krueger M31

=> assign projection information for Bundesmeldenetz M28 to raster data

```
gdal_translate -of GTiff -a_srs ESRI::Austria_BMN_MGI_M28.prj //
```

```
-co "TFW=YES" -co "COMPRESS=LZW" ortho.tif orthoBMN_M28.tif
```

=> raster transformation from Bundesmeldenetz M28 to Gauss-Krueger M31

```
gdalwarp -s_srs ESRI::Austria_BMN_MGI_M28.prj //
```

```
-t_srs ESRI::Austria_GK_MGI_M31.prj -of GTiff //
```

```
-co "TFW=YES" orthoBMN_M28.tif orthoGK_M31.tif
```

example for transformation with ogr2ogr:

(for syntax and supported formats please see the ogr-manuals)

source: shapefileBMNM28.shp in Bundesmeldenetz M28

target: Bundesmeldenetz M34

```
ogr2ogr -s_srs ESRI::Austria_BMN_MGI_M28.prj //
```

```
-t_srs ESRI::Austria_BMN_MGI_M34.prj //
```

```
shapefileBMNM34.shp shapefileBMNM28.shp
```
